

Specification for

Butyl acetate for industrial use

Confirmed
January 2011

Committees responsible for this British Standard

The preparation of this British Standard was entrusted by the Chemicals Standards Policy Committee (CIC/-) to Technical Committee CIC/51, upon which the following bodies were represented:

British Pharmacopoeia Commission

British Society of Perfumers

Chemicals Industries Association

Royal Society of Chemistry

Solvents Industry Association Ltd.

This British Standard, having been prepared under the direction of the Chemicals Standards Policy Committee, was published under the authority of the Board of BSI and comes into effect on 31 August 1990

© BSI 11-1999

First published May 1934
Second edition March 1950
Third edition December 1956
Fourth edition June 1965
Fifth edition August 1990

The following BSI references relate to the work on this standard:
Committee reference CIC/51
Draft for comment 89/50508 DC

ISBN 0 580 18571 0

Amendments issued since publication

Amd. No.	Date	Comments

Contents

	Page
Committees responsible	Inside front cover
Foreword	ii
<hr/>	
1 Scope	1
2 Description	1
3 Sampling and size of sample	1
4 Colour	1
5 Density	1
6 Distillation range	1
7 Residue on evaporation	1
8 Water content	1
9 Acidity	1
10 Ester content	1
<hr/>	
Appendix A Determination of distillation range	2
Appendix B Determination of acidity	2
Appendix C Determination of ester content	3
<hr/>	
Publication(s) referred to	Inside back cover
<hr/>	

Foreword

This British Standard, which has been prepared under the direction of the Chemicals Standards Policy Committee, supersedes BS 551:1965 which is withdrawn. In this revision of BS 551 the requirement for residue on evaporation has been made more stringent and the requirement for relative density has been replaced by one for density at 20 °C. In addition, some of the appendices describing test methods in the previous edition have been replaced by references to general test methods.

This British Standard is related to ISO 1386:1983 but is not equivalent in technical content. ISO 1386 is published by the International Organization for Standardization (ISO). ISO 1386 lists various general test methods, which correspond to those to which reference is made in this British Standard, and it also describes methods for the determination of acidity and for the determination of ester content which are similar to those described in Appendix B and Appendix C, respectively, of this British Standard. ISO 1386 does not specify limits for any of the properties of butyl acetate or other solvent acetates.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, pages 1 to 4, an inside back cover and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.

1 Scope

This British Standard specifies requirements for butyl acetate suitable for industrial purposes.

NOTE The titles of the publications referred to in this standard are listed on the inside back cover.

2 Description

The material shall be clear and free from matter in suspension, as assessed by visual inspection, and shall consist essentially of the acetic ester of butan-1-ol ($\text{CH}_3\text{COOCH}_2\text{CH}_2\text{CH}_2\text{CH}_3$).

3 Sampling and size of sample¹⁾

A representative sample of the material measuring not less than 0.5 L shall be taken from the bulk for the purpose of examination in accordance with this standard. The sample shall be placed in a clean, dry and air-tight, ground glass-stoppered bottle, or screw-capped bottle fitted with a polyethylene cone insert, of such capacity that it is almost filled by the sample.

NOTE 1 When it is necessary to seal the container, care should be taken to avoid the risk of contaminating the contents in any way.

NOTE 2 Sufficient ullage should be left in the bottle to avoid excessive pressure changes that could arise from temperature variations during storage and handling. About 10 % ullage is recommended.

4 Colour

The colour of the material shall not exceed 15 Hazen colour units when measured by the method described in BS 5339.

5 Density

The density of the material at 20 °C, measured by the method described in BS 4522, shall be not lower than 0.878 g/mL and not higher than 0.881 g/mL.

6 Distillation range

When the material is distilled by the method described in BS 4591, modified as described in Appendix A, the initial boiling point at 101.3 kPa pressure shall be not lower than 124.0 °C and the dry point at 101.3 kPa pressure shall be not higher than 129.0 °C.

7 Residue on evaporation

The residue on evaporation of the material shall not exceed 0.0020 % (*m/m*) when determined by the method described in BS 4524.

8 Water content

The material shall not contain more than 0.10 % (*m/m*) of water when determined by the method described in clause 2 of BS 2511:1970 using 20 mL of the material.

9 Acidity

The acidity of the material, calculated as acetic acid (CH_3COOH), shall not exceed 0.010 % (*m/m*) when determined by the method described in Appendix B.

10 Ester content

The material shall contain not less than 97.0 % (*m/m*) of esters, calculated as butyl acetate ($\text{CH}_3\text{COOC}_4\text{H}_9$), when determined by the method described in Appendix C.

¹⁾ Detailed information on the sampling of liquid chemical products is given in BS 5309-1 and 5309-3.

Appendix A Determination of distillation range

Determine the distillation range, in terms of the initial boiling point and the dry point, by the method described in BS 4591, using the following thermometer and temperature corrections.

- Thermometer* (5.1.2 of BS 4591:1990). Use a thermometer designated F150C/100 complying with BS 593.
- Corrections to be applied to observed temperatures* (9.1.2 of BS 4591:1990). If the corrected barometric pressure deviates from 101.3 kPa apply corrections to the observed temperatures by subtracting 0.037 °C for every 0.1 kPa above 101.3 kPa, or adding 0.037 °C for every 0.1 kPa below 101.3 kPa.

NOTE These corrections are valid only for pressures above 93.3 kPa.

Appendix B Determination of acidity

B.1 Principle

A test portion is diluted with 95 % (V/V) ethanol (or methylated spirits) and titrated with standard volumetric sodium hydroxide solution, using phenolphthalein as indicator.

B.2 Reagents

B.2.1 General

During the analysis, use only reagents of recognized analytical grade, only methylated spirits complying with BS 3591, and only water complying with grade 3 of BS 3978.

B.2.2 Ethanol or industrial methylated spirits, 95 % (V/V).

NOTE The use of industrial methylated spirits is governed by The Methylated Spirits Regulations, 1983 (S.I. 1983 No. 252). It is not permissible to use duty-free ethanol, received under the provisions of The Alcoholic Liquor Duties Act 1979, Section 10, for purposes for which industrial methylated spirits is an acceptable alternative.

B.2.3 Sodium hydroxide, standard volumetric solution, $c(\text{NaOH}) = 0.100 \text{ mol/L}$.

B.2.4 Phenolphthalein, 5 g/L ethanolic solution. Dissolve 0.5 g of phenolphthalein in 100 mL of the ethanol or industrial methylated spirits (B.2.2) and add the sodium hydroxide solution (B.2.3) until a pale pink coloration is obtained.

B.3 Apparatus

B.3.1 Ordinary laboratory apparatus

B.3.2 Conical flask, of 250 mL capacity, of borosilicate glass, fitted with a ground glass stopper carrying a guard tube containing sodium hydroxide on an inert support (soda lime).

B.3.3 Burette, of 10 mL capacity, graduated in 0.02 mL divisions, complying with class A of BS 846.

B.4 Procedure

B.4.1 Test portion

Take 50 ± 0.5 mL of the sample, measured at 20 °C.

B.4.2 Determination

Place 50 mL of the ethanol or industrial methylated spirits (B.2.2) in the conical flask (B.3.2), add 0.5 mL of the phenolphthalein solution (B.2.4) and add the sodium hydroxide solution (B.2.3) until a pale pink coloration is obtained. Add the test portion (B.4.1), mix and titrate the mixture with the sodium hydroxide solution, using the burette (B.3.3), until a pink coloration, persisting for at least 10 s, is obtained. Stopper the flask and swirl its contents after each addition of sodium hydroxide solution.

B.5 Expression of results

The acidity A , expressed as a percentage by mass of acetic acid (CH_3COOH), is given by the equation:

$$A = \frac{0.006 V_1}{\rho \times 50} \times 100$$

i.e.

$$A = \frac{0.012 V_1}{\rho}$$

where

- V_1 is the volume of the sodium hydroxide solution used for the determination (in mL);
- ρ is the density of the sample at 20 °C (determined by the method described in BS 4522) (in g/mL);
- 0.006 is the mass of acetic acid corresponding to 1.00 mL of sodium hydroxide solution, $c(\text{NaOH}) = 0.100 \text{ mol/L}$ (in g).

Report the result to two significant figures.

B.6 Test report

The test report shall include the following information:

- a complete identification of the sample;
- a reference to the method used, i.e. BS 551, Appendix B;
- the results expressed in accordance with B.5;
- any unusual features noted during the determination;
- any operation not included in this appendix or regarded as optional.

Appendix C Determination of ester content

C.1 Principle

The esters present in a test portion are saponified with excess ethanolic potassium hydroxide solution and the excess is determined by titration with standard volumetric hydrochloric acid solution, using phenolphthalein as indicator.

C.2 Reagents

C.2.1 General

During the analysis, use only reagents of recognized analytical grade, only methylated spirits complying with BS 3591, and only water complying with grade 3 of BS 3978.

C.2.2 Potassium hydroxide, 56 g/L solution in 95 % (V/V) ethanol or 95 % (V/V) industrial methylated spirits.

NOTE The use of industrial methylated spirits is governed by The Methylated Spirits Regulations, 1983 (S.I. 1983 No. 252). It is not permissible to use duty-free ethanol, received under the provisions of The Alcoholic Liquor Duties Act 1979, Section 10, for purposes for which industrial methylated spirits is an acceptable alternative.

C.2.3 Hydrochloric acid, standard volumetric solution, $c(\text{HCl}) = 1 \text{ mol/L}$.

C.2.4 Phenolphthalein, 5 g/L ethanolic solution. Prepare as described in **B.2.4**.

C.3 Apparatus

C.3.1 Ordinary laboratory apparatus

C.3.2 Two conical flasks, of borosilicate glass, capacity 250 mL, fitted with ground glass stoppers.

C.3.3 Two reflux condensers, water-cooled, with ground glass joints to fit conical flasks (**C.3.2**).

C.3.4 Weighing pipette, capacity 10 mL.

C.4 Procedure

C.4.1 Test portion

Using the weighing pipette (**C.3.4**), transfer between 2.7 g and 3.2 g of the sample, weighed to the nearest 0.001 g, to a conical flask (**C.3.2**) containing 50.0 mL of the potassium hydroxide solution (**C.2.2**), introduced by means of a one-mark pipette.

C.4.2 Blank test

Introduce 50.0 mL of the potassium hydroxide solution (**C.2.2**), using the same one-mark pipette referred to in **C.4.1**, into the second conical flask (**C.3.2**).

C.4.3 Determination

Attach a reflux condenser to each conical flask and heat the two flasks for 1 h in a boiling-water bath. Withdraw the flasks, still carrying their condensers, and immerse them in cold running water. When cool, wash down the inside of each condenser with two 20 mL portions of water, collecting the washings in the flask. Disconnect the flasks and wash each joint with a further 20 mL of water, again collecting the washings in the appropriate flask.

Add 0.5 mL of the phenolphthalein solution (**C.2.4**) to each flask and immediately titrate the contents of each flask in turn with the hydrochloric acid solution (**C.2.3**) until the pink colour is just discharged.

C.5 Expression of results

The ester content E , expressed as a percentage by mass of butyl acetate ($\text{CH}_3\text{COOC}_4\text{H}_9$), is given by the equation:

$$E = \frac{116.2 (V_0 - V_1)}{1000 \times m} \times 100$$

$$\text{i.e. } E = \frac{11.62 (V_0 - V_1)}{m}$$

where

V_0 is the volume of the hydrochloric acid solution used for the titration of the blank (in mL);

V_1 is the volume of the hydrochloric acid solution used for the titration of the test solution (in mL);

m is the mass of the test portion (in g);

116.2 is the relative molecular mass of butyl acetate.

Report the result to one decimal place.

C.6 Test report

The test report should include the following information:

- a complete identification of the sample;
- a reference to the method used, i.e. BS 551, Appendix C;
- the results expressed in accordance with **C.5**;
- any unusual features noted during the determination;
- any operation not included in this appendix or regarded as optional.

Publication(s) referred to

BS 593, *Specification for laboratory thermometers.*

BS 846, *Specification for burettes.*

BS 2511, *Methods for the determination of water (Karl Fischer method).*

BS 3591, *Specification for industrial methylated spirits.*

BS 3978, *Specification for water for laboratory use.*

BS 4522, *Method for determination of absolute density at 20 °C of liquid chemical products for industrial use.*

BS 4524, *Method for determination of residue on evaporation on a water bath.*

BS 4591, *Method for determination of distillation characteristics of organic liquids (other than petroleum products).*

BS 5309, *Methods for sampling chemical products.*

BS 5309-1, *Introduction and general principles.*

BS 5309-3, *Sampling of liquids.*

BS 5339, *Method of measurement of colour in Hazen units (platinum-cobalt scale) of liquid chemical products.*

ISO 1386, *Solvent acetates for industrial use — Methods of test²⁾.*

²⁾ Referred to in the foreword only.

BSI — British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover. Tel: 020 8996 9000. Fax: 020 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: 020 8996 9001. Fax: 020 8996 7001.

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact the Information Centre. Tel: 020 8996 7111. Fax: 020 8996 7048.

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration. Tel: 020 8996 7002. Fax: 020 8996 7001.

Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

If permission is granted, the terms may include royalty payments or a licensing agreement. Details and advice can be obtained from the Copyright Manager. Tel: 020 8996 7070.