BS 89-6:1990 EN 60051-6: 1989 IEC 51-6:1984

Direct acting indicating analogue electrical measuring instruments and their accessories —

Part 6: Specification for special requirements for ohmmeters (impedance meters) and conductance meters

This European Standard EN 60051-6 has the status of a British Standard

UDC 621.317.73.037.33:620.1



Cooperating organizations

The European Committee for Electrotechnical Standardization (CENELEC), under whose supervision this European Standard was prepared, comprises the National Committees of the following countries.

Austria Italy Belgium Luxemburg Denmark Netherlands Finland Norway France Portugal Germany Spain Greece Sweden Iceland Switzerland Ireland United Kingdom

This British Standard, was published under the authority of the Board of BSI and comes into effect on 31 August 1990

© BSI 07-1999

First published, as BS 89, October 1919 Second August 1926 Third edition September 1937 Fourth edition February 1954 Fifth edition March 1977 Published, as BS 89-6, August 1990

The following BSI references relate to the work on this standard: Committee reference PEL/13 Draft for comment 88/33511 DC

ISBN 0 580 18467 6

Amendments issued since publication

Amd. No.	Date of issue	Comments

Contents

	Page
Cooperating organizations	Inside front cover
National foreword	ii
Foreword	2
Brief history	2
Text of EN 60051-5	5
National appendix W	Inside back cover

National foreword

This British Standard has been prepared under the direction of the Power Electrical Engineering Standards Policy Committee and is the English language version of EN 60051-6 "Direct acting indicating analogue electrical measuring instruments and their accessories — Part 6: Special requirements for ohmmeters (impedance meters) and conductance meters, published by the European Committee for Electrotechnical Standardization (CENELEC). It is identical with IEC publication 51-6 published by the International Electrotechnical Commission (IEC).

This Part of BS 89 together with Parts 1, 2, 3, 4, 5, 7, 8 and 9 of this Standard supersedes BS 89:1977, which is withdrawn. BS 89 comprises the following Parts, which will be the English language version of the listed European Standards.

European Standard	Corresponding Part of BS 89
EN 60051-1	Part 1 Specification for definitions and general requirements common to all Parts
EN 60051-2	Part 2 Specification for special requirements for ammeters and voltmeters
EN 60051-3	Part 3 Specification for special requirements for wattmeters and varmeters
EN 60051-4	Part 4 Specification for special requirements for frequency meters
EN 60051-5	Part 5 Specification for special requirements for phase meters, power faction meters and synchroscopes
EN 60051-6	Part 6 Specification for special requirements for ohmmeters (impedance meters) and conductance meters
EN 60051-7	Part 7 Specification for special requirements for multi-function instruments
EN 60051-8	Part 8 Specification for special requirements for accessories
EN 60051-9	Part 9 Recommended test methods

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, the EN title page, pages 2 to 8, an inside back cover and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.

ii © BSI 07-1999

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN 60051-5

November 1989

UDC 621.317.73.037.33:620.1

Key words: Electrical measuring instruments; analogue indicating instruments; direct acting measuring instruments; accessories for electrical measuring instruments; ohmmeters; impedance meters; conductance meters

English version

Direct acting indicating analogue electrical measuring instruments and their accessories Part 6: Special requirements for ohmmeters (impedance meters) and conductance meters

(IEC 51-6:1984: edition 4)

Appareils mesureurs électriques indicateurs analogiques á action directe et leurs accessoires Sixiéme partie: Prescriptions particulières pour les ohmmétres (les impédancemétres) et les conductancemétres (CEI 51-6:1984: édition 4) Direkt wirkende anzeigende elektrische Meßgeräte und ihr Zebehör Meßgeräte mit Skalenanzeige

Teil 6: Spezielle Anforderungen für Widerstands — (Scheinwiderstands -) und Leitfähigkeits-Meßgeräte (IEC 51-6:1984: Ausgabe 4)

This European Standard was ratified by CENELEC on 11 September 1989. CENELEC members are bound to comply with the requirements of the CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CENELEC Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French and German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to CENELEC Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxemburg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B-1050 Brussels

Brief history

The text of IEC-Publication 51-6 (4th edition — 1984) was submitted to the CENELEC members for unique acceptance.

Technical text

The text of the International Standard IEC 51-6 (4th edition — 1984) was approved by CENELEC on 11 September 1989 as a European Standard.

The following dates are applicable:

- latest date of announcement of the EN at national level (doa): 1990-03-01
- date of latest publicationof a new harmonizedstandard (dop): 1990-09-01
- date of withdrawal of conflicting national standards

standards (dow): 1990-09-01

Foreword

- 1) The formal decisions or agreements of the IEC on technical matters, prepared by Technical Committees on which all the National Committees having a special interest therein are represented, express, as nearly as possible, an international consensus of opinion on the subjects dealt with.
- 2) They have the form of recommendations for international use and they are accepted by the National Committees in that sense.
- 3) In order to promote international unification, the IEC expresses the wish that all National Committees should adopt the text of the IEC recommendation for their national rules in so far as national conditions will permit. Any divergence between the IEC recommendation and the corresponding national rules should, as far as possible, be clearly indicated in the latter.

Preface

This standard has been prepared by IEC Technical Committee No. 85: Measuring Equipment for Basic Electrical Quantities (former Sub-Committee 13B: Electrical Measuring Instruments).

This fourth edition replaces the third edition of IEC Publication 51.

This standard constitues Part 6.

The general layout for the revised Publication 51 is as follows:

- Part 1: Definitions and General Requirements Common to all Parts;
- Part 2: Special Requirements for Ammeters and Voltmeters:
- Part 3: Special Requirements for Wattmeters and Varmeters;
- Part 4: Special Requirements for Frequency Meters;
- Part 5: Special Requirements for Phase Meters, Power Factor Meters and Synchroscopes;
- Part 6: Special Requirements for Ohmmeters (Impedance Meters) and Conductance Meters;
- Part 7: Special Requirements for Multi-function Instruments;
- Part 8: Special Requirements for Accessories;
- Part 9: Recommended Test Methods.

Parts 2 to 9 are not complete in themselves and shall be read in conjunction with Part 1.

All of these parts are arranged in the same format and a standard relationship between subject and clause number is maintained throughout. In addition, tables, figures and appendices add a suffix to the part number in order to differentiate the parts. This re-arrangement will assist the reader of IEC Publication 51 to distinguish information relating to the different types of instruments.

The text of this standard is based upon the following documents:

Six Months' Rule	Report on Voting
13B(CO)89	13B(CO)98

Further information can be found in the Report on Voting indicated in the table above.

Contents

		Page
Brief	fhistory	2
Fore	word	2
1	Scope	5
2	Definitions	5
3	Description, classification and compliance	e 5
4	Reference conditions and intrinsic errors	5
5	Nominal range of use and variations	5
6	Further electrical and mechanical	
	requirements	6
7	Constructional requirements	6
8	Information, general markings and	
	symbols	6
9	Markings and symbols for terminals	6
10	Tests to prove compliance with this	
	standard	7
Арре	endix A-6 Suggestions for routine tests	8

© BSI 07-1999 3

4 blank

1 Scope

1.1 to 1.8 See Part 1.

1.9 Part 6 of the standard does not apply to resistivity meters (specific resistance meters), insulation resistance meters used in energized circuits or conductivity meters (specific conductance meters).

2 Definitions

See Part 1.

3 Description, classification and compliance

3.1 Description

Ohmmeters shall be described:

- **3.1.1** According to their method of operation as given in Sub-clause **2.2** of Part 1.
- **3.1.2** According to whether they measure resistance values by a two-terminal or a four-terminal method.
- **3.1.3** According to whether they have a linear scale or a non-linear scale.

3.2 Classification

Ohmmeters shall be classified in one of the accuracy classes denoted by the following class indices:

0.05, 0.1, 0.2, 0.5, 1, 1.5, 2, 2.5, 3, 5, 10, 20.

3.3 Compliance with the requirements of this standard

- **3.3.1** and **3.3.2** See Part 1.
- **3.3.3** For impedance meters and for instruments not scaled in units of resistance or conductance, the manufacturer's instructions shall be followed.

4 Reference conditions and intrinsic errors

4.1 Reference conditions

- **4.1.1** to **4.1.3** See Part 1.
- **4.1.4** The requirements of Table I-1 concerning ripple, distortion, peak-factor and frequency do not apply to ohmmeters.
- **4.2 Limits of intrinsic error: fiducial value** See Part 1.

4.2.1 Correspondance between intrinsic error and accuracy class

See Part 1.

4.2.2 Fiducial value

The fiducial value for an ohmmeter corresponds to: **4.2.2.1** The indicated value for non-linear scale ohmmeters.

The class index is marked using Symbol E-3 given in Table III-1 (see Part 1, Clause 8).

4.2.2.2 The span for linear scale ohmmeters.

The class index is marked using Symbol E-10 given in Table III-1 (see Part 1, Clause 8).

4.3 Rated values

- **4.3.1** When a rated voltage is stated, the open circuit voltage at the measuring terminals shall not differ from the rated voltage by more than 10 % of the rated voltage.
- **4.3.2** When a rated voltage across a given value of test resistance is stated, the voltage shall not differ from the rated voltage by more than 10 % of the rated voltage.
- **4.3.3** When a maximum (or a minimum) value is stated, it shall not exceed (or be less than) the stated voltage at any permissible supply voltage and at any setting of the controls and adjustments which are accessible to the user.
- **4.3.4** When a rated, maximum or minimum current is stated, the requirements of Sub-clauses **4.3.1** to **4.3.3** shall apply, substituting current for voltage.

5 Nominal range of use and variations

5.1 Nominal range of use

5.1.1 and **5.1.2** See Part 1.

5.1.3 The requirements of Table II-1 concerning ripple, distortion, peak-factor and frequency do not apply to ohmmeters.

5.2 Limits of variations

See Part 1.

5.2.1 to **5.2.4** See Part 1.

5.2.5 Ohmmeters which employ batteries shall operate correctly with the batteries having any value of voltage and internal resistance within the ranges stated by the manufacturer. When the preliminary adjustments specified by the manufacturer have been carried out, any variations caused by changes of the battery characteristics shall not cause the instrument to indicate outside its accuracy class.

5.3 Conditions for the determination of variations

5.3.1 and **5.3.2** See Part 1.

5.3.3 The variations of ohmmeters intended for intermittent use shall be determined immediately after pre-conditioning, if any.

© BSI 07-1999 5

6 Further electrical and mechanical requirements

6.1 Voltage tests, insulation tests and other safety requirements

See Part 1.

6.2 Damping

The requirements of Part 1 do not apply to ohmmeters.

6.3 Self-heating

For the recommended test, see Part 9, Sub-clause **4.14**.

6.3.1 to **6.3.3** The requirements of Part 1 do not apply to ohmmeters.

6.3.4 See Part 1.

6.3.5 Ohmmeters intended for continuous use shall comply with their accuracy requirements after being connected to an open circuit for any time after the completion of the specified pre-conditioning period, if any.

They shall similarly comply with their accuracy requirements after being connected to a short circuit.

6.3.6 The requirements of Sub-clause **6.3.5** also apply to ohmmeters intended for intermittent use except that the time after connection shall be up to 30 s for ohmmeters having hand-driven rotary generators and up to 5 min for all other ohmmeters intended for intermittent use.

6.4 Permissible overloads

The requirements of Part 1 do not apply to ohmmeters.

6.5 Limiting values of temperature

See Part 1.

6.6 Deviation from zero

There are no requirements relating to deviation from zero for ohmmeters.

7 Constructional requirements

7.1 Sealing to prevent access

See Part 1.

7.2 Scales

7.2.1 and 7.2.2 See Part 1.

7.2.3 Direction of deflection

The direction of deflection for ohmmeters is not specified.

7.2.4 Limits of the measuring range

7.2.4.1 to **7.2.4.3** See Part 1.

7.2.4.4 For ohmmeters with non-linear scales, the method of identifying the limits of the measuring range by the omission of subdivisions outside the measuring range (Figure 1-1) shall not be used.

7.2.4.5 The measuring range shall correspond to at least 50 % of the scale length.

7.3 Preferred values

To be agreed between manufacturer and user.

7.4 Adjuster(s), mechanical and/or electrical See Part 1.

7.5 Effects of vibration and shock

See Part 1.

8 Information, general markings and symbols

8.1 Information

See Part 1.

8.1.1 The open-circuit voltage or the voltage across a test resistance of given value and the short-circuit current are rated values and shall be stated as required by Item e) of Sub-clause **8.1** in Part 1.

8.2 and 8.3 See Part 1.

9 Markings and symbols for terminals

9.1 to **9.3** See Part 1.

9.4 Special markings for terminals

9.4.1 Single-function two-terminal ohmmeters shall have the terminal which, when in use, is positive relative to the other terminal, marked with Symbol F-46 (+).

9.4.2 Single-function four-terminal ohmmeters shall have the current terminal which, when in use, is positive relative to the other current terminal, marked with Symbol F-46 (+).

9.4.3 The requirements of Sub-clauses **9.4.1** and **9.4.2** need not apply to multi-function instruments where other uses of the terminals may require different markings.

9.4.4 Ohmmeters having (an) accessory(ies)

The terminals intended to be connected to an external measuring circuit shall be marked in accordance with Sub-clauses **9.4.1** to **9.4.3**. The terminal(s) on the ohmmeter which is intended to be connected to (a) terminal(s) on the accessory(ies) shall be marked with an arabic numeral(s).

The manufacturer may select any convenient and non-conflicting numeral(s). Pairs of terminals which are intended to be connected together shall carry the same numeral.

$10 \ \mathrm{Tests}$ to prove compliance with this standard

See Part 1 and Appendix A-6.

Appendix A-6 Tests

A-6 1 Suggestions for routine tests

Test for intrinsic error for resistance measurement (Clause 4).

Test for rated, maximum or minimum voltage or current (Clause 4).

Test for variation due to position (Clause 5, Table II-1).

Voltage test (Sub-clause 6.1).

National appendix W

The United Kingdom participation in the preparation of this European Standard was entrusted by the Power Electrical Engineering Standards Policy Committee (PEL/-) to Technical Committee PEL/13 upon which the following bodies were represented:

Association of Consulting Engineers

Association of Supervisory and Executive Engineers

Department of Energy (Electricity Division)

Department of Trade and Industry (National Physical Laboratory)

Department of Trade and Industry (National Measurement Accreditation Service)

Electrical Power Engineers' Association

Electricity Supply Industry in England and Wales

Engineering Teaching Equipment Manufacturers' Association

GAMBICA (BEAMA) Ltd.

General Electric Company Limited

Institution of Electrical Engineers

BS 89-6:1990 EN 60051-6: 1989 IEC 51-6:1984

BSI — British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover. Tel: 020 8996 9000. Fax: 020 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: 020 8996 9001. Fax: 020 8996 7001.

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact the Information Centre. Tel: 020 8996 7111. Fax: 020 8996 7048.

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration. Tel: 020 8996 7002. Fax: 020 8996 7001.

Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

If permission is granted, the terms may include royalty payments or a licensing agreement. Details and advice can be obtained from the Copyright Manager. Tel: 020 8996 7070.

BSI 389 Chiswick High Road London W4 4AL